



## Refrigerated recirculation baths “Frigiterm-TFT-10-S” and “Frigiterm-TFT-30-S”

ADJUSTABLE TEMPERATURE FROM -10 °C TO 100 °C. STABILITY: 0 °C TO 100 °C,  $\pm 0,1$  °C / -10 °C,  $\pm 0,1$  °C.  
 ADJUSTABLE TEMPERATURE FROM -30 °C TO 100 °C. STABILITY: 0 °C TO 100 °C,  $\pm 0,1$  °C / -30 °C,  $\pm 0,2$  °C.  
 SET ERROR :  $\pm 1$  °C. RESOLUTION: 0.1 °C.

### SAFETY:

STANDARD DIN 12876. SAFETY OVER TEMPERATURE  
 THERMOSTAT WITH ADJUSTABLE MANUAL RESET.  
 LOW LIQUID LEVEL SENSOR PROTECTION.

### FEATURES

Maximum working volume to maintain maximum temperature: 8 litres.  
 AISI 304 stainless steel top and lid with an inner tank of AISI 304 stainless steel.  
 Complete with a pump for internal and external liquid circulation with inlet and outlet connectors. A drain tap is placed at the side of the unit.  
 A hermetically sealed compressor is mounted on anti-vibration mounts.  
**A RS-232 interface for connection to a printer or computer.**

### MODELS

	Part No.	Capacity litres	Control range °C	Height / Width / Depth (usable) cm	Height / Width / Depth (exterior) cm	Pump Pressure / Flowrate H <sub>2</sub> O	Power W	Compressor power H.P.	Weight Kg
FRIGITERM-10-S	3000552	8	-10 + 100	12 20 14	66 36 46	150 mbar-12 l/min	1150	1/8	28
FRIGITERM-30-S	3000553	8	-30 + 100	12 20 14	66 36 46	150 mbar-12 l/min	1460	3/8	30

