



Water double distillation “L-4B”

DISTILLATION CAPACITY: 4 LITRES/HOUR.



FEATURES

Made completely from borosilicate glass with protective case that has easy access to the heater elements and glass parts.

Automatic function and continuous production.

Produces high quality double distilled water free from pyrogen and metallic ions.

It functions through a dual distillation process:

The distilled water from the first stage is collected by the heater reservoir of the second stage, that starts the double distiller function when when the water’s level is optimum, thus providing double distilled process.

Protection with a safety thermostat is activated if there is insufficient cooling water.

Reactivated automatically when the water supply is re-established.

Water flow stop if there is an electrical fault.

If it is required to store the distilled water and to prevent over filling, the system stops, switches off power and disconnects the water flow when is full.

Voltage: 230 V / 1, 50/60 Hz = 26.8 A

MODEL

Part No.	Distillation capacity l/h	Water consumption l/min	Conductivity at 20 °C	Height/Width/Depth cm	Power W	Weight Kg
4903010	4	2	0.5 µs/cm	48 69 40	2x3000	22



SPARES

Heater element made of quartz. Part No **4903011**

Glass still, borosilicate glass (the equipment comes with 2 condensers. Price provided is for 1 spare condenser). Part No. **4903012**

Condenser, borosilicate glass (the equipment comes with 2 condensers. Price provided is for 1 spare condenser). Part No. **4903014**