



# Rocking Mixer "Vibromatic"

DIGITAL ELECTRONIC CONTROL OF SPEED AND TIME.



**Optimum shaking frequency: 950 oscillations per minute**

## APPLICATIONS

Dissolution, extractions and homogenisation.

## FEATURES

Electronic control from 100 to 950 oscillations per minute. (1900 vibrations) and timer from 1 to 999 minutes or continuous operation.

Oscillation amplitude: 8 mm.

Easily detachable arms equipped with 8 clamps that allow all types of tubes and flask with diameters of between 5 to 50 mm can be held in position.

Maximum load: 4 kg.

## CONTROL PANEL

1. Digital display indicator of osc./min. and time.
2. Parameter display selector.
3. Parameter selector, speed or time.
4. Push button increase value.
5. Push button decrease value.
6. Push button start-stop.



## MODEL

Part No.	Oscillations p.m.	Maximum capacity Kg	Height / Width / Depth (exterior) cm	Power W	Weight Kg
<b>7000384</b>	<b>100 - 950</b>	<b>4</b>	<b>23 77 27</b>	<b>34</b>	<b>11</b>



## ACCESSORIES

### 2 in 1. Platform support for Erlenmeyer flasks.

**Platform support for Erlenmeyer flasks**, made from AISI 304 stainless steel with clip adapter position holes for 50 ml to 1000 ml flasks. Platform dimensions: 38 cm long x 19 cm wide.

Weight: 2 Kg.

Platform capacity:

- 18 Erlenmeyer flasks of 50 ml.
- 12 Erlenmeyer flasks of 100 ml.
- 8 Erlenmeyer flasks of 250 ml.
- 6 Erlenmeyer flasks of 500 ml.
- 3 Erlenmeyer flasks of 1000 ml.

Part No. **3001221**



*Model Vibromatic with adapter platform.*

### Adapters for Erlenmeyer flasks.

Made from tempered stainless steel.

Part No.

- |                |             |          |
|----------------|-------------|----------|
| <b>1001003</b> | Adapter for | 50 ml.   |
| <b>1000978</b> | Adapter for | 100 ml.  |
| <b>1000979</b> | Adapter for | 250 ml.  |
| <b>1000980</b> | Adapter for | 500 ml.  |
| <b>1000981</b> | Adapter for | 1000 ml. |

