

Water and oil baths "Univeba"

WATER BATH: ADJUSTABLE TEMPERATURE FROM AMBIENT +5 °C TO 110 °C STABILITY ±2 °C.
OIL BATH: ADJUSTABLE TEMPERATURE FROM AMBIENT +5 °C TO 200 °C STABILITY ±3 °C.

SAFETY:

CONFORMS TO THE DIN STANDARD 12877 BY INCORPORATING A MANUALLY RESET OVER TEMPERATURE SAFETY CUT-OUT.

APPLICATIONS

To be used with a rotary evaporator or as a stand alone Bains Marie bath.

FEATURES

Tank interior and exterior case made of AISI 304 stainless steel. The heater element is embedded in a protective INCOLOY stainless steel shield.

CONTROL PANEL

Illuminated main power switch indicator lamp. Hydraulic temperature thermostat regulator synchronised with an indicator lamp. Safety thermostat cut out indicator lamp.



MODELS

Part No.	Maximum Temperature °C	Capacity litres	Ø (usable)	Height cm	Height / Widht / Depth (exterior) cm			Power W	Weight Kg
3000400	110	2.5	18	13	19	22	27	390	4
3000401	200	2.5	18	13	19	22	27	640	4

ACCESSORIES MADE OF STAINLESS STEEL

- 1- Heating element cover shelf.
 Part No. 6000033
- 2- Reduction ring cover lid of 110, 80, 60 and 37 mm Ø. With a thermometer location hole in the lid. Part No. 7004001
- **3- Tube rack** for 24 haemolysis tubes up to 13 mm Ø. Part No. **7004002**
- 4- Tube support rack for 24 tubes up to 18 mm Ø. Part No. 7000541

5- Thermometer.

Part No.

1000100 up to 100 °C. 1095250 up to 250 °C.