



# Bank of oil and water baths "Precisbat"

ADJUSTABLE TEMPERATURES FROM AMBIENT +5 °C UP TO 200 °C, STABILITY ± 2 °C.  
INDEPENDENT TEMPERATURE CONTROL FOR EACH POSITION.

## FEATURES

Inner vessel made of AISI 304 stainless steel with the external case made of AISI 304 stainless steel.

The heater element is embedded in stainless steel INCOLOY alloy, that is corrosion and heat resistant.

Each position has a lid with concentric reduction rings of; 105, 80, 60 and 40 mm in Ø.

An adjustable support frame is mounted at the back of the unit to facilitate the mounting and support of flasks, condensers and other apparatus, etc.

Capacity: 2 litres per position.

## CONTROL PANEL

**Independent control for each position.**

Mains ON/OFF with luminous "ON" indicator lamp for each position.

Hydraulic thermostat temperature control synchronised with the "ON" indicator lamp.



## MODELS

Part No.	Temperature maximum °C	Number of places	Height / Width / Depth (usable each position) cm			Height / Width / Depth (exterior) cm			Power W	Weight Kg
			Height	Width	Depth	Height	Width	Depth		
6001462	200	2	12	14	12	19	35	29	1300	5.5
6001472	200	4	12	14	12	19	67	29	2560	10
6001482	200	6	12	14	12	19	100	29	4200	15

## ACCESSORIES



**Perforated shelf** (One per tank) made of AISI 304 stainless steel. Part No. **6000011**



**Clamp for supporting flasks and condensers.** Part No. **7000403**



**Thermometer up to 220 °C.** Part No. **1095250**



**Bosshead for supporting clamps.** Part No. **1000069**

**Silicone oil** 4 liters. Temperature up to 300°C. Viscosity 50 mm<sup>2</sup>/s at 25 °C. Melting point 318 °C. Part No. **1000027**