



## Refrigerated recirculation baths “Frigiterm-TFT-10” and “Frigiterm-TFT-30”

ADJUSTABLE TEMPERATURE FROM -10 °C TO 100 °C. STABILITY: 0 °C TO 100 °C, ±0.1 °C / -10 °C, ±0.1 °C.

ADJUSTABLE TEMPERATURE FROM -30 °C TO 100 °C. STABILITY: 0 °C TO 100 °C, ±0.1 °C / -30 °C, ±0.2 °C.

SET ERROR : ±1 °C. RESOLUTION: 0.1 °C.

### SAFETY:

STANDARD DIN 12876. SAFETY OVER TEMPERATURE  
THERMOSTAT WITH ADJUSTABLE MANUAL RESET.  
LOW LIQUID LEVEL SENSOR PROTECTION.

### FEATURES

Maximum working volume to maintain maximum temperature: 8 litres.

AISI 304 stainless steel top and lid with an inner tank of AISI 304 stainless steel.

Complete with a pump for internal and external liquid circulation with inlet and outlet connectors. A drain tap is placed at the side of the unit.

A hermetically sealed compressor is mounted on anti-vibration mounts.

**A RS-232 interface for connection to a printer or computer.**

### MODELS

	Part No.	Capacity litres	Control range °C	Height / Width / Depth (usable) cm	Height / Width / Depth (exterior) cm	Pump Pressure / Flowrate H <sub>2</sub> O	Power W	Compressor power H.P.	Weight Kg
FRIGITERM-10	3000546	8	-10 + 100	12 20 14	36 66 44	150 mbar-12 l/min	1150	1/8	28
FRIGITERM-30	3000547	8	-30 + 100	12 20 14	36 66 44	150 mbar-12 l/min	1460	3/8	30



NEW  
DESIGN

REGULATION  
SYSTEM  
B

SANS CFC  
CFC FREE

RS232

USB