



Bath circulators "Digiterm-TFT-200"

WITH IMMERSION THERMOSTAT DIGITERM-TFT-200.

CUVETTES SET OF 20 AND 27 L.

FROM AMBIENT +5 °C TO 200 °C. STABILITY ±0.1 °C. SET ERROR ±2 °C. RESOLUTION 0.1 °C.



SAFETY: CONFORMS TO THE DIN 12876. STANDARD. ADJUSTABLE OVER TEMPERATURE SAFETY CUT OFF WITH ADJUSTABLE MANUAL RESET. LOW LIQUID LEVEL CUT OFF. ELECTRICAL FAULT ALARM.

FEATURES

Temperature sensor probe Pt 100.

Heating element made of stainless steel INCOLOY, resistant to high temperatures and corrosive environments.

Circulation pump with flow rate, suitable for external temperature control for: (Polarimeters, refractometers, viscometers, etc).

Cooling coil to maintain ambient temperatures, using tap water.

External temperature control connection using a Pt 100 probe (see page104).

External metal case made of AISI 304 stainless steel.

Handles at the side and drain tap.



MODELS	Part No.	Temperatura Range °C	Cuvettes Capacity litres	Height / Width / Depth (interior) cm			Height / Width / Depth (exterior) cm			Pressure mbar	Pump Pump rate l/min	Power W	Weight Kg
				1	2	3	4	5	6				
TFT-200 20	3000550	200	20	15	30	29	36	55	35	150	12	2060	10
TFT-200 27	3000551	200	27	20	30	29	41	55	35	150	12	2060	12

ACCESSORIES see page 104.

ACCESSORIES for the DIGITERM-S-150 and DIGITERM-TFT-200. Made of AISI 304 stainless steel.



1. Gable lid. Part No. **3001295**

2. Lifting rack support. Capacity 3 tube racks. Part No. **1001296**

3. Tube racks for lifting rack support.

Part No.	For Ø tubes mm	Capacity Rack tubes	Height/Width/Depth (exterior) cm		
1001202	13	36	8	8.2	23.6
1001203	16	24	8	8.2	23.6
1001204	20	24	8	8.2	23.6

