



Centrifuge Angle rotor "Cencom II"

WITH ANGLE ROTOR FOR 6 X 15 ml TUBES AND 6 ADDITIONAL ADAPTERS FOR 15 ML FALCON TUBES.
DIGITAL ELECTRONIC CONTROL OF SPEED AND TIME. ADJUSTABLE SPEED UP TO 4000 r.p.m. (1790 R.c.f.)

SAFETY:

SAFETY ACCORDING TO EN. 61010.2.020 SAFETY MICRO-SWITCH THAT DISCONNECTS THE POWER TO THE MOTOR WHEN THE LID IS OPENED.
PROTECTIVE FUSE LOCATED AT THE BACK OF THE INSTRUMENT.

APPLICATIONS

General laboratory use and teaching.

FEATURES

External case made from coated ABS plastic.

Rubber suspended motor, reduces any motor vibrations.

Fixed angle 6 place rotor with identification code.

Transparent polycarbonate lid that allows the user to see inside the centrifuge.

Speed selection from 1000 to 4000 r.p.m. in 500 r.p.m. steps.

Time selection from 1' to 60' in steps of 1'.

CONTROL PANEL

Digital display of speed and time.

Push button Start-Stop.

Push button selector for speed and time.

Push button increase value.

Push button decrease value.



Cross section view of the angle rotor showing bucket and bucket support.



MODEL

Part No.	Tube capacity ml	Height/Ø (exterior) cm	Max. speed r.p.m.	Max. R.c.f.	Power W	Weight Kg
7002240	6 x 15	28 26	4000	1790	80	4.5

Supplied complete with 6 x 15 ml tubes with adapters and 6 adapters for 15 ml Falcon tubes.

ACCESSORY

Adapter. Suitable for 13 Ø x 75 mm VAC tubes.
Rotor capacity, 6 adapters.

Part No. **1001556**