



Multi-parameter water quality meter "MP-2006"

LARGE TOUCH SCREEN. TO MEASURE PH, ORP, CONDUCTIVITY, TDS, SALINITY, DISSOLVED OXYGEN, IONS & TEMPERATURE SUPPLIED WITH ELECTRODES: OF CONDUCTIVITY, PH, DISSOLVED OXYGEN AND TEMPERATURE PROBE.



FEATURES

5.7 inches touch screen.

Capacity to store up to 2200 sets of data. GLP method. Possibility of storing, printing and deleting measuring data. USB and RS-232 ports for PC connection.

Measuring modes: continuous, timing and balance measuring modes.



TECHNICAL DATA

	Range	Accuracy	Resolution
pH:	-2 to +19,999	±0,002 FS	0,001
ORP:	±1999,99 mV	±0,03 FS	0,01 mV
Conductivity:	0,001 µS to +199,9mS	±0,5 FS	0,001µS
TDS:	0,000 mg/L to 19.99g/L	±0,5 FS	0,001 mg/L
Salinity:	(0,0 to 8,00)%	±0,1%	0,1%
Dissolved oxygen:	0,00 to 19.99 mg/L	±0,5 mg/L	0,01 mg/L
Ions:	0 to 19990(ug/L, mol/L)	±0,5%	±1
T ^a :	-0,5 to +135	±0,5 FS	0,1

MODEL

Code	Height / Width / Depth cm	Power	Weight Kg
4120700	29 20 7	230V/50-60Hz	1

ACCESSORIES

Standard electrodes of pH, conductivity and temperature. See page 247.

Special electrodes:

Code	Electrode type	Working temperature	Body material	Measure mm	Code	Electrode type	Working temperature	Body material	Measure mm
4120183	Platinum	0-50°	Glass	Ø 12 x 120	4120189	Calcium	5-60°	Glass	Ø 12 x 120
4120184	Platinum-2	0-50°	Glass	Ø 12 x 120	4120190	Nitrate	5-60°	Glass	Ø 12 x 120
4120185	Antimony	0-50°	ABS	Ø 12 x 120	4120191	Copper	5-60°	Glass	Ø 12 x 120
4120186	Tungsten	0-50°	Glass	Ø 12 x 120	4120192	Chloride	5-60°	Glass	Ø 12 x 120
4120187	Silver	0-50°	ABS	Ø 12 x 120	4120193	Oxygen	5-40°	ABS	Ø 12 x 120
					4120194	Reference	5-55°	Glass	Ø 12 x 120